

ZURRUM MF ESD S1P SRC low



COD ARTICOL

02010557 XX XXX



00 GRI



40 ALBASTRU



10 VERDE

DESCRIERE

Lightweight safety shoe in a modern, sporty design. The upper is made of breathable textile. The oil-resistant non-slip outsole is made of double-density polyurethane and ensures maximum safety at every step. In addition, the shoes are equipped with a comfortable inner insole, which guarantees comfort while walking. The absorption of energy in the heel area absorbs shocks and reduces the feeling of fatigue in the feet. Thanks to a light, and modern toe cap made of fiberglass, the footwear meets the requirements of the EN ISO 20345: 2011 standard. This means that the feet are protected against compression with a force of up to 15 kN or the fall of a load of up to 20 kg from a height of 1 m. The feet are also protected from below, thanks to the composite antipuncture midsole. The shoes do not contain metal parts and are equipped with the ESD function. Therefore, it is an ideal model for indoor spaces and sensitive environments, where it is necessary to prevent sparks from electrostatic discharge or for rooms equipped with a safety frame. Thanks to the modern materials used in production of this model, the total weight of the shoes does not exceed 495 g (half-pair size 42). Minimalist design and modern colors will go great with most of Cerva's workwear collection.

STANDARDE

EN ISO 20345:201 1 EN 61340-5-1:201 6



S1 P SRC

ZURRUM MF ESD S1P SRC low

COD ARTICOL

02010557 XX XXX

MATERIAL

Materialul lamelei de protecție: compozit

Material superior: textile

Material bombu: fibră de sticlă

Material talpă: double density polyurethane

Material pentru căptușeala încălțăminte: poliester

CULORI

00 - gri

10 - verde

40 - albastru

MĂRIMI

035 - 35

036 - 36

037 - 37

038 - 38

039 - 39

040 - 40

041 - 41

042 - 42

043 - 43

044 - 44

045 - 45

046 - 46

047 - 47

048 - 48

049 - 49

050 - 50

CARACTERISTICI



Greutatea articolului: 495g

STANDARDE

EN ISO 20345:2011 / S1 P SRC

EN 61340-5-1:2016